

| Nomenclature | Mini Adaptive Automatic Fire Ext 100gm SS SP Red w/200mm barrel | Mini Adaptive Automatic Fire Ext 200gm SS SP Red w/200mm barrel | Mini Adaptive Automatic Fire Ext 300gm SS SP Red w/200mm barrel | Mini Adaptive Automatic Fire Ext 400gm SS SP Red w/200mm barrel | Mini Adaptive Automatic Fire Ext 500gm SS SP Red w/200mm barrel |
|------------------------------------|---|---|---|---|---|
| Stored Pressure/Cartridge | Stored Pressure | Stored Pressure | Stored Pressure | Stored Pressure | Stored Pressure |
| Agent | Fluoroketone (FK- 5-1-12) | Fluoroketone (FK- 5-1-12) | Fluoroketone (FK- 5-1-12) | Fluoroketone (FK- 5-1-12) | Fluoroketone (FK- 5-1-12) |
| Product Code | CF-001340AC | CF-001342AC | CF-001344AC | CF-001346AC | CF-001348AC |
| Certification type | PED, UKCA-PED, BSI Tested | PED, UKCA-PED, BSI Tested | PED, UKCA-PED, BSI Tested | PED, UKCA-PED, BSI Tested | PED, UKCA-PED, BSI Tested |
| PED | Yes | Yes | Yes | Yes | Yes |
| UKCA-PED | Yes | Yes | Yes | Yes | Yes |
| Gross Weight (approx.) | 0.822 Kg | 1.05 Kg | 1.20 Kg | 1.39 Kg | 1.58 Kg |
| Net Mass (approx.) | 100 Gm | 200 Gm | 300 Gm | 400 Gm | 500 Gm |
| Total Height of Fire Ext. (approx) | 148 mm | 248 mm | 240 mm | 295 mm | 350 mm |
| Maximum Volume Covered | 0.130 m ³ | 0.260 m ³ | 0.390 m ³ | 0.520 m ³ | 0.650 m ³ |
| Discharge Mechanism | Automatic QBD* | Automatic QBD* | Automatic QBD* | Automatic QBD* | Automatic QBD* |
| Can Construction | Deep Drawn & MIG Welded | Deep Drawn & MIG Welded | Deep Drawn & MIG Welded | Deep Drawn & MIG Welded | Deep Drawn & MIG Welded |
| Valve/Cap Construction | Machining | Machining | Machining | Machining | Machining |
| External Coating | Epoxy Polyester Powder | Epoxy Polyester Powder | Epoxy Polyester Powder | Epoxy Polyester Powder | Epoxy Polyester Powder |
| Warranty in Years | 5 | 5 | 5 | 5 | 5 |
| Min. Discharge Time | 1 to 3 sec | 1 to 3 sec | 1 to 3 sec | 1 to 3 sec | 1 to 3 sec |
| Working Pressure | 10 Bar / 12 Bar | 10 Bar / 12 Bar | 10 Bar / 12 Bar | 10 Bar / 12 Bar | 10 Bar / 12 Bar |
| Dia. of Shell (OD) | 40 mm | 40 mm | 50 mm | 50 mm | 50 mm |
| Operating Temp. | -30°C to +60°C | -30°C to +60°C | -30°C to +60°C | -30°C to +60°C | -30°C to +60°C |
| Hydrostatic Test Pressure | 35 Bar | 35 Bar | 35 Bar | 35 Bar | 35 Bar |
| Body Thickness | 1.2 mm | 1.2 mm | 1.2 mm | 1.2 mm | 1.2 mm |